



High end professional print production. **Versafire EP.**



Key features at a glance

- Reliable output of up to 4,500 A3 sheets/hours or 135 A4 sheets/minute (simplex)
- Automatic inline registration and calibration
- Inline sensors for precise color control and color consistency
- Fine detail reproduction with 2,400 × 4,800 dpi with low-temperature/high-gamut toner
- Vacuum suction feeder for secure media transport
- Consistent production speed even with thick or textured media
- Large-format duplex banner printing up to 330 × 1,030 mm (12.99 × 40.55 in)

- Print applications with paper weight up to 470 gsm, even on textured media
- High availability due to tray capacity of max. 18,100 sheets

Output Security

Deciding whether to print a job on a digital device or with offset is not always easy. The Prinect Digital Frontend controller ensures both full flexibility and consistency. The same PDF interpreter and color engines are used for output to the computer-to-plate system (e.g. Suprasetter® from Heidelberg®) and the Versafire when using the Prinect workflow system.

Technical data Versafire EP

Features	Versafire EP
Engine	2,400 × 4,800 dpi Wax-based PxP™ toner Automatic inline registration and calibration and color control Vacuum suction feeder Media identification unit Enhanced toner transfer system for structured media (AC/DC) 17-inch touchscreen Capacity of up to 18,100 sheets
Controller	Prinect Digital Frontend or EFI Fiery E-46A/86A
Media format min. width × length	100 × 140 mm simplex (3.94 × 5.51 in), 140 × 200 mm duplex (5.51 × 7.87 in)
Media format max. width × length	330 × 487 mm (12.99 × 19.17 in), duplex large capacity tray (max. 470 gsm) 330 × 700 mm (12.99 × 27.55 in), duplex large capacity tray (max. 300 gsm) 330 × 1,030 mm (12.99 × 40.55 in), duplex with bypass tray (max. 220 gsm) 330 × 1,260 mm (12.99 × 49.61 in), simplex with bypass tray (max. 220 gsm)
Printing speed	4,500 A3 sheets/hour or 135 A4 pages/minute (simplex) optional 3,720 A3 sheets/hour or 115 A4 pages/minute (simplex)
Print material*	Plain paper, coated paper (gloss and matt), recycled paper, pre-printed offset, letterhead, pre-punched, tab stock, OHP (transparency), translucent paper, envelope, textured paper, metallized, synthetic, water-resistant, magnetic or label (adhesive) substrates, NCR (carbon copy)
Grammage	52–470 gsm (duplex)
Average monthly print volume	Up to 500,000 A3 sheets/month (simplex)
Weight	max. 1,000 kg (engine)
Dimensions (W × D × H)	2,520 × 990 × 1,870 mm (99.21 × 38.98 × 73.62 in)
Power consumption	< 9,000 Watts
Options	Up to 3 large-capacity trays, cover interposer, multi-folding unit, perfect binder, ring binder, booklet finisher and trimmer, high-capacity stacker

* Not all media approved – please refer to the latest media qualification list

Heidelberg Druckmaschinen AG

Kurfuersten-Anlage 52 – 60

69115 Heidelberg

Germany

Phone +49 6221 92-00

Fax +49 6221 92-6999

heidelberg.com

Printed on Versafire.

Heidelberg, the Heidelberg logotype, Versafire and Prinect are trademarks of Heidelberg Druckmaschinen AG.

All other trademarks are property of their respective owners.

Subject to technical modifications and other changes.

Find out more about Versafire:
heidelberg.com/Versafire