

Technical data.

palamides delta.

	delta502	delta703	delta705xs	delta1005
No. of ups	2	3	5	5
Max. sheet size, width × length (cm)				
1 up	51 × 30	76 × 30	76 × 30	110 × 32
2 ups	23.5 × 30	33.5 × 30	33.5 × 30	50 × 32
3 ups		23.5 × 30	23.5 × 30	32 × 32
4 ups			17.5 × 30	23 × 32
5 ups			14.8 × 30	21 × 32
Min. sheet size, width × length (cm) mit Kleinformateinrichtung	11 × 9.5 9 × 6.5	11 × 9.5 9 × 6.5	6 × 6.5	12 × 11 10.5 × 9
Max. pile height (mm)	150	150	150	150
Min. pile height (mm)	20	20	20	20
Max. speed (m / min)	200	200	200	200
Max. speed (m / min)	15	15	15	15
Max. output (piles / h)	1,200	1,800	3,000	3,000
Bänderbreite (mm)	5	5	3	5
Pressing force (N)	35,000	35,000	35,000	35,000
Infeed height (cm)	40 – 105	40 – 105	40 – 105	40 – 105
palamides control system	Bedienpult mit Display	Bedienpult mit Display	Bedienpult mit Display	Bedienpult mit Display
Power consumption (kVA)				
3 × 400V, 50 / 60Hz, 50 A	6	6	6	6
3 × 230V, 50 / 60Hz, 63 A	6	6	6	6
Compressed air consumption at 6 bar (l / min)	350	350	350	350

Technical data subject to machine configuration, job, format, substrate, and possibly other factors.
The combination of individual features may vary from one country to another.

1 cm equals 0.3937 inches.