

Technical data.

Stahlfolder BH 66.

	Feeder			Folding units		
	Flat pile	Round continuous	Pallet	1 st station 66	2 nd station 66 / 56	3 rd station 56
Version	Manual or automated					
Max. sheet size, width × length (cm)	66 × 104	66 × 128	66 × 104			
Min. sheet size, width × length (cm)	14 × 18	14 × 18	14 × 18			
Paper weight (g/m ²)	40 – 250	40 – 250	40 – 250			
Max. pile height (cm)	80	8	120			
Number of buckle plates				4 or 6	4 or 6	4
Max. fold length (cm) position 1						
Swing-deflector buckle plate				62	58	46
Combination buckle plate				58	46	46
Min. fold length (cm)						
Swing-deflector buckle plate				5.5	5.5	5.5
Combination buckle plate				6	6	6
Max. speed (m/min.)				200	180	180
Min. speed (m/min)				25	25	25
Diameter of folding rollers (mm)				44	44	44
MCT control system	control panel with display or touchscreen	control panel with display or touchscreen	control panel with display or touchscreen		control panel	control panel
Power consumption (kVA)						
3 × 400 V, 50/60 Hz, 50 A	incl. pump 5.7 / 6.3	incl. pump 6.6 / 7.4	incl. pump 7.0 / 7.8	in feeder	1.6	1.6
3 × 230 V, 50/60 Hz, 63 A	5.7 / 6.3	6.6 / 7.4	7.0 / 7.8	in feeder	1.6	1.6

Technical data subject to machine configuration, job, format, substrate and possibly other factors.
The combination of individual features may vary from one country to another.

1 cm equals 0.3937 inches.