



Key performance

- 3-ply innovative design, no fabric underneath top surface
- Extra smash resistance
- Soft carcass for easy dressing
- Very versatile with wide range of substrates

MAIN APPLICATION

Packaging

Printec TCB1 is available in 3-ply, 1,96 mm thickness.



Co-development with Heidelberg Asia Pacific, under exclusivity.



The product at a glance

INK COMPATIBILITY	Conventional
THICKNESS mm	1,96 ± 0,02
PRINTING SURFACE COLOUR	NBR Blue
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250
SURFACE ROUGHNESS (Ra micron)	0,8 - 1,2
ELONGATION (%)	<0,9
TENSILE STRENGHTS (N/mm)	>70
COMPRESSIBLE LAYER	Microsphere closed cells
ADDITIONAL INFORMATION	
APPLICATION	Packaging

FOR ANY FURTHER DETAILS AND FOR A QUOTATION
PLEASE REFER TO YOUR SALES MANAGER
OR EMAIL US AT: printingsm@trelleborg.com

www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions. Trelleborg Printing Solutions is committed to the ongoing development of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.